

## **STANDARD 30 YARD ROLL-OFF RECYCLING CONTAINER SPECIFICATIONS**

### **STANDARD DECK**

- 3/16 PL. Floor Sheet (Pieced)
- 3" Structural Channel on 20" centers
- 3/16 PL. Gussets on every other Cross Member
- 2 x 6 x 3/16 tube one piece main rail
- (4) 8" dia. x 10" LG. Heavy Duty Wheel
- 4" OD x 6" LG. w/1 1/2" Pin Front Roller and grease fitting
- Hook Plate 1" Plate 6" x 15"
- Cable Hook 1 1/4" Plate (w/lifetime guarantee)
- 1 1/2" Plate Solid Bull Nose

### **FRONT & SIDES**

- 11 Ga. Steel
- 3 x 4 x 11 Ga. Top Tube
- 11 Ga. 3 x 5 Formed 4 Way Bend Side Stiffener on 24" centers. Columns have notches at bottom to prevent moisture retention.
- 11 Ga. Formed Corner Post Wraps around for extra strength and stability

### **REAR CORNER POSTS**

- Latch Side 3" x 4" x 11" Ga. Tube
- Hinge Side 3" x 8" x 7" Ga. Formed 4 Way Bend

### **REAR DOOR**

- 11 Ga. Sheet w/ 3" x 4" x 11 Ga. Tube Frame & 3/8" Safety Chain
- Hinges 1/2" x 9" x 7" & 1/2" x 3" x 9" Plates with 2" OD Mechanical Tube Bushings with Grease Fittings and 1 3/16" Cold Rolled Pin
- Non-Sagging Door must rest on floor of container
- Rear Door entry has a large opening to eliminate any bridging of cardboard or any other recyclable material

### **DOOR LOCK**

- Semi-automatic Cam Locking system w/3 Cams & Self-Aligning Keeper and with a Vertical Lift Handle (flat bar) to assure customer safety.

### **TOP**

- 11 Ga. Steel with 3 openings on each side or a total of 6 per container.
- Double wall plastic sliding door (30" x 30") equipped with a (lockable) sliding bolt latch.

### **OPTIONAL DIVIDERS**

- 14 Ga. steel reinforced with 2" x 2" x 1/4" angle  
Locking pins (3/4" round bar) are inserted through the side of the container to lock divider in place.
- Each divider has an 11 Ga. fixed plate welded above to eliminate spillage into the next compartment. This enables you to obtain the fullest capacity of that compartment.