CONTAINERS

Recycling Containers



FEATURING:

- Lifetime Guarantee on Hook and Hook Plate
- Rudco Roll-Offs feature tube main rails with solid bullnose
- All containers are primed and painted in one of ten standard colors
- Formed front corner posts for added strength
- Non-Sagging Door is designed to rest on floor of container
- Large "V" notches in each vertical support column prevents moisture retention
- Vertical Lift Handle with Semi-Automatic Cam Locking System

ALL PRODUCTS ARE BUILT RUDCO TOUGH IN THE USA



Rental Program And Financing Available


www.rudco.com


Toll Free: 1.800.828.2234 • E-Mail: sales@rudco.com

CONTAINERS

Recycling Container







Recycling Container Specifications

30 X 30 SLIDING DOORS.-

SIZE	DOORS PER SIDE	HEIGHT INSIDE	HEIGHT OUTSIDE	WIDTH OVERALL	LENGTH OVERALL	APPROX. WEIGHT
12 YD	2	55"	78-1/2"	96"	(A) 12' 9"	3900 LBS.
18 YD	3	55"	78-1/2"	96"	(A) 16' 9"	4500 LBS.
25 YD	4	55"	78-1/2"	96"	(A) 22' 9"	5000 LBS.

STANDARD DECK

- 3/16" PL. Floor Sheet
- 3" Structural Channel on 20" Centers
- 3/16" PL. Gussets on every other Cross Member
- 6" x 2" x 3/16" Tube One Piece Main Rail
- Four 8" diameter x 10" LG. Heavy Duty Wheels
- 4" OD x 6" LG Front Roller w/11/2" Pin and Grease Fitting
- 1" Certified Hook Plate (w/lifetime guarantee)
- 1¼" Certified Plate Cable Hook (w/lifetime guarantee)
- 1½" Plate Solid Bullnose

FRONT AND SIDES

- 11 Ga. Sheet
- 11 Ga. One Piece Formed Dog House
- 3" x4" x 11 Ga. Top Tube
- 11 Ga. 3" x 5" Formed 4-way Bend Side Stiffener on 24" Centers.
 Columns have notches at bottom to prevent moisture retention
- 11 Ga. Formed Corner Post wraps around for extra strength

REAR CORNER POST

- Latch Side 3" x 4" x 11 Ga. Tube
- Hinge Side 3" x 8" x 3/16" Formed Stiffener 4-way Bend

REAR DOOR

- 11 Ga. Sheet w/ 3" x 4" x 11 Ga. Tube Frame and 3/8" Safety Chain
- Hinges ½" x 9" x 9" and ½" x 3" x 9" Plates with 2" OD Mechanical Tube Bushings with Grease Fittings and one 3/16" Cold Rolled Pin
- Non-Sagging Door is designed to rest on the floor of the container

DOOR LOCK

 Semi-automatic Cam Locking system w/3 Cams & Self-Aligning Keeper

and with a Vertical Lift Handle (flat bar) to assure customer safety

HOOF

11 Ga. Steel With Maximum of 4 openings per side for a total of 8 per container.

DIVIDER (OPTIONAL)

- 11 Ga. Steel reinforced with 2" x 2" x 1/4" angle. Locking pins are inserted through the side of the container to lock divider in place.
- Each divider has an 11 Ga. fixed plate welded above to eliminate spillage into the next compartment. This enables you to obtain the fullest capacity of that compartment.

NOTE: Recycle Containers can be stacked 5 or 6 per load. This saves freight cost per container. However, when stacking and unstacking, doors have to be removed and re-hung, and the containers may be scratched or dented. We cannot be responsible for this happening since it is unavoidable when stacking containers.

RUDCO RESERVES THE RIGHT TO REVISE, AMEND AND IMPROVE IT'S EQUIPMENT WITHOUT NOTICE





CORPORATE OFFICE: 114 E. Oak Rd. • Vineland, NJ 08360 • Ph:1.856.691.0800 • Fax: 1.856.696.0084

MAILING ADDRESS: P.O. Box 705 • Vineland, NJ 08362

www.rudco.com